

23/5/2018

SAFETY DATA SHEET

1. IDENTIFICATION OF PRODUCT AND OF THE COMPANY	
Trade name: Company:	Super Thin Flexible MDF Ventech Australia 32 Thornycroft Street Campbellfield VIC 3061 Australia
Phone number: e-mail:	1300 714 105 sales@ventech.com.au

2. HAZARDS IDENTIFICATION

No hazards are described during handling of boards.

During manipulation of boards (cutting, machining, sanding, ..) dust wood or traces of formaldehyde could be liberated.

Risk of weak irritation to the skin or respiratory system could be possible in some of these cases.

3. COMPOSITION / INFORMATION OF THE COMPONENTS

CAS No	Hazards symbols	R-Phrases	Concentration
- Timber			80-84 %
- Urea Formaldehyde Resin	Xn	R40-43	9 - 12 %
- Water			4 - 8 %
- Paraffin wax			0,5-1,0 %

4. FIRST AID MEASURES

In case of fire or irritation, move exposed people to a well-ventilated place.

If it is necessary, summon doctor.

5. FIRE FIGHTING MEASURES

Special hazards:	Not classed as flammable. Combustion will evolve carbon dioxide (CO ₂) or carbon monoxide (CO).
Protective equipment:	A self contained breathing apparatus and suitable protective clothing should be worn in big fires.
Extinguishing agents:	Water, foam or dry powder.

6. ACCIDENTAL RELEASE MEASURES

Not applicable

7. HANDLING AND STORAGE Safe handling advice: Do not storage boards higher than 4 m. Boards could fall off. Avoid carry boards without mechanical help. Back injuries could be occasionated. Requirements for storage rooms: Storage area has to be indoor, well-ventilated and damp free.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION



Última revisión: 02/01/2010

SAFETY DATA SHEET

Applicable as long as boards are manipulated (sanding, machining, cutting...)

Occupational exposure limits

See local requirements, if occupational exposure limits are avaliable.

Dust wood:	TLV-TWA:	5 mg/m^3
Formaldehyde:	TLV-STEL:	0,3 ppm, 0,37 mg/m ³

Technical meausures:

Where suitable engineering controls are not fitted or inadequate, wear suitable protective equipment.

Personal protection:

Respiratory protec .:	Wear suitable respiratory protective equipment if exposure to levels above
	the occupational exposure limit is likely.
Eye protection:	Wear eye/face protection
Hand protection:	Wear suitable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	solid
Colour:	Beige
Odour:	wood
Boiling point:	no data
Melting point:	no data
Autoignition temperature:	175 °C
Explosion limits:	lower: not applicable
_	higher: not applicable
Density:	780-840 kg/m ³ ot
Solubility in water:	n applicable
Explosive properties:	not applicable not
Oxidizing properties:	applicable

10. STABILITY AND REACTIVITY

Hazardous reactions (conditions to avoid): None known

Hazardous reactions (materials to avoid): None known

Hazardous decomposition products: See Fire Fighting Measures.

11. TOXICOLOGICAL INFORMATION

Acute toxicity (irritation, sensisation, etc.): No data

Delayed or chronic toxicological effects: Risk of weak irritation to skin or respiratory system could be possible.



Última revisión: 02/01/2010

SAFETY DATA SHEET

12. ECOLOGICAL INFORMATION	
Degradability:	100 %
Mobility:	Boards are not soluble in water
Ecotoxicity:	LC 50: no data IC 50: no data

13. DISPOSAL CONSIDERATIONS

Disposal should be in accordance with local, state or national legislation.

14. TRANSPORT INFORMATION

Road transport ADR/RID:not applicableMaritime transport IMDG:not applicable

Air transport ICAO/IATA: not applicable

15. REGULATORY INFORMATION

Classification:	not applicable
Hazards labels:	not applicable
R-phrases:	not applicable
S-phrases:	not applicable
-	

Hazardous ingredients: Formaldehyde (< 0,008 %)

16. OTHER INFORMATION

This data sheet was prepared in accordance with Directive 91/155/EC

The above information is accurate to our knowledge and shall describe our product under the aspect of safety. They are not meant to guarantee specific properties of the product.

The existing regulations are to be observed by our customers at their own responsability.

 Full text of R-phrases: R40 – Possible carcinogenic effects. R43- Possibility of sensitization by skin contact. R50/53-Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
 Full text of classification referred to in section 3: Xn- Harmful, N-Dangerous for the environment.